Vol 6. No.S3

## Temporal changes in mechanical properties of steel fiber reinforced and polypropylene fiber reinforced aggregate recycling concrete

Hasan Baylavli and İlker Bekir

Hitit University, Turkey

## **Abstract**

In this study, recycling aggregates were obtained from polypropylene fiber-reinforced concrete produced in different types and proportions. Polypropylene fiber-reinforced welding concrete was broken in a jaw crusher at the end of 120 days, and recycling aggregates of 0-4mm, 4-15mm and 15- 22, 4 mm dimensions were obtained. With the polypropylene fiber-reinforced recycling aggregates obtained, concrete is produced again. Polypropylene fiber reinforced aggregate recycling concrete has been added in two (2) different ratios of steel fiber. Steel fiber reinforced concrete produced has been awaited for three years in the laboratory environment. The compressive strength, tensile splitting strength, elasticity modulus, bending strength, and bending strength deformation of the suspended concrete were investigated. The compression, tensile splitting, and bending strength and the modulus values of elasticity have increased slightly depending on the time. The abrasion and water imbibition values of hardened concrete samples were also measured. The addition of steel fiber has improved abrasion strength. The water imbibition ratio has also increased with the addition of steel fiber.

Received: July 07, 2022; Accepted: July 14, 2022; Published: July 31, 2022

## **Biography**

Hasan Baylavli works in Hitit University Construction Technology and Building Audit Programs, in Çorum, Turkey as Research Assistant. Completed associate degree program in 1997 in Gazi University Çorum Vocational School Construction Program. Graduated from Pamukkale University, Faculty of Engineering and Department of Civil Engineering in 2000. Works in these subjects: self-compacting concretes, fiber-reinforced concretes and recycling. Furthermore, have studies in the fields of university campus planning, green campus and energy-efficiency in buildings.